

Metallurgical microscopes KERN OKO-1



Stage OKO



Illumination unit

PROFESSIONAL LINE MET

The fully-equipped reflected and transmitted light microscope for numerous applications in metallurgy

Features

- This device is a professional, versatile, metallurgical microscope, which is used in testing metals and analysing surfaces
- The KERN OKO 178 is a combi variant of LED incident illumination and LED transmitted illumination. A height-adjustable 1.25 Abbe condenser which can be centred as well as a field diaphragm for complete professional Köhler illumination are part of the standard version.
- An open, mechanical angle table is integrated as standard
- A simple polarising unit (analyser and polariser) is included with delivery
- A large selection of accessories, such as, for example, eyepieces and further objectives are available for longer working distances
- A protective dust cover, eye cups, as well as multi-lingual user instructions are included in the scope of delivery
- A C-Mount adapter is required to connect a camera. You can select this adapter from the following model outfit list
- Please find detailed information in the following model outfit list

Scope of application

- Metallurgy, material testing, quality assurance

Applications/Samples

- Opaque and thick samples, workpieces (surfaces, fold lines, coatings)

Technical data

- Infinity optical system
- Quintuple nosepiece
- Siedentopf 30° inclined/360° rotatable
- Diopter adjustment: Both-sided
- Overall dimensions W×D×H 550×200×460 mm
- Net weight basic configuration approx. 14,5 kg

STANDARD



| Model | Standard configuration | | | | |
|---------------------|------------------------|-----------------|-------------------|-----------------|----------------------------------|
| | Tube | Eyepiece | Objective quality | Objectives | Illumination |
| KERN OKO 178 | Trinocular | HWF 10×/∅ 22 mm | Infinity Plan | 5x/ 10x/20x/50x | 5 W LED (incident + transmitted) |

Metallurgical microscopes KERN OKO-1

| Model outfit | | Model KERN | Order number | |
|--|--|------------|--------------|--|
| | | OKO 178 | | |
| Eyepieces (30 mm) | HWF 10×/∅ 22 mm (adjustable) | ✓ | OBB-A 1491 | |
| | HWF 10×/∅ 22 mm (reticule 0,1 mm) (adjustable) | ✓ | OBB-A 1523 | |
| Infinity Plan objectives for long working distance | 5×/0,13 W.D. 16,04 mm | ✓ | OBB-A 1525 | |
| | 10×/0,25 W.D. 18,48 mm | ✓ | OBB-A 1526 | |
| | 20×/0,40 W.D. 8,35 mm | ✓ | OBB-A 1527 | |
| | 50×/0,70 (spring-loaded) W.D. 1,95 mm | ✓ | OBB-A 1528 | |
| | 80×/0,80 (spring-loaded) W.D. 0,85 mm | ○ | OBB-A 1530 | |
| | 100×/0,85 (dry) W.D. 3,00 mm | ○ | OBB-A 1531 | |
| Trinocular tube | <ul style="list-style-type: none"> • Siedentopf 30° inclined/360° rotatable • Interpupillary distance 48 – 76 mm • Light distribution 100:0 | ✓ | | |
| Mechanical stage for transmitted illumination | <ul style="list-style-type: none"> • Stage size W×D 182×140 mm • Travel 77×52 mm • Coaxial coarse and fine focusing knobs | ✓ | | |
| Reflected illumination unit | Polarising unit (Incl. analyser, polariser and blue filter slide) | ✓ | | |
| Condenser | Abbe N.A. 1,25 (aperture diaphragm) | ✓ | OBB-A 1380 | |
| Koehler illumination | 5 W LED spare bulb (transmitted) | ✓ | OBB-A 1589 | |
| Illumination polarising unit | 5 W LED spare bulb (incident) | | | |
| Polariser | for transmitted illumination | ✓ | OBB-A 1470 | |
| Colour filters for transmitted illumination | Blue | ✓ | OBB-A 1170 | |
| | Green | ○ | OBB-A 1188 | |
| | Yellow | ○ | OBB-A 1165 | |
| | Grey | ○ | OBB-A 1183 | |
| C-Mount | 1× | ○ | OBB-A 1514 | |
| | 0,75× | ○ | OBB-A 1590 | |
| | 0,5× (focus adjustable) | ○ | OBB-A 1515 | |

✓ = Included with delivery

○ = Option

Pictograms

| | | |
|--|---|---|
| 360° rotatable microscope head | Fluorescence illumination for compound microscopes With 3 W LED illumination and filter | USB 3.0 digital camera For direct transmitting of the picture to a PC |
| Monocular Microscope For the inspection with one eye | Phase contrast unit For a higher contrast | WLAN data interface For transmitting of the picture to a mobile display device |
| Binocular Microscope For the inspection with both eyes | Darkfield condenser/unit For a higher contrast due to indirect illumination | HDMI digital camera For direct transmitting of the picture to a display device |
| Trinocular Microscope For the inspection with both eyes and the additional option for the connection of a camera | Polarising unit To polarise the light | PC software To transfer the measurements from the device to a PC |
| Abbe Condenser With high numerical aperture for the concentration and the focusing of light | Infinity system Infinity corrected optical system | Automatic temperature compensation For measurements between 10 °C and 30 °C |
| Halogen illumination For pictures bright and rich in contrast | Zoom magnification For stereomicroscopes | Protection against dust and water splashes IPxx: The type of protection is shown in the pictogram cf. DIN EN 60529:2000-09, IEC 60529:1989+A1:1999+A2:2013 |
| LED illumination Cold, energy-saving and especially long-life illumination | Auto-focus For automatic control of the focus level | Battery operation Ready for battery operation. The battery type is specified for each device. |
| Incident illumination For non-transparent objects | Parallel optical system For stereomicroscopes, enables fatigue-proof working | Battery operation rechargeable Prepared for a rechargeable battery operation |
| Transmitting illumination For transparent objects | Integrated scale In the eyepiece | Plug-in power supply 230V/50Hz in standard version for EU. On request GB, AUS or USA version. |
| Fluorescence illumination For stereomicroscopes | SD card For data storage | Integrated power supply unit Integrated in microscope. 230V/50Hz standard EU. More standards e.g. GB, AUS or USA on request. |
| Fluorescence illumination for compound microscopes With 100 W mercury lamp and filter | USB 2.0 digital camera For direct transmitting of the picture to a PC | Package shipment The time required to manufacture the product internally is shown in days in the pictogram. |

Abbreviations

| | | |
|---|---|--|
| C-Mount Adapter for the connection of a camera to a trinocular microscope | LWD Long Working Distance | SWF Super Wide Field (Field number at least \varnothing 23 mm for 10 \times eyepiece) |
| FPS Frames per second | N.A. Numerical Aperture | W.D. Working Distance |
| H(S)WF High (Super) Wide Field (Eyepiece with high eye point for wearers of glasses) | SLR camera Single-Lens Reflex camera | WF Wide Field (Field number up to \varnothing 22 mm for 10 \times eyepiece) |

Your KERN specialist dealer: