

JAYSON **ELECTRO-MAGNET**

The JAYSON offers unparalleled flexibility and comfort of use.

- Open access for viewing
- Good leg extension
- Easy to grip "slim" handle
- Lighter weight than standard models

Magnetic Particle Inspection "Hand-held portable yoke" manufactured to comply with:- EN ISO 9934-3:2002

FREQ

MODELS AVAILABLE IAYSON 230V AC JAYSON 110V AC JAYSON 230 and 110 Volt as above respectively

1.75 Amps Max 3.1 Amps Max

CURRENT

50/60 Hz Standard Unit 50/60 Hz Standard Unit 50/60 Hz

NOTES

25mm x 18mm

50%

Fixed Output all Models

Interchangeable leads gives the operator choice of desired voltages

ORDER CODE **IAYSON 230V** JAYSON 110V **JAYSON Bi VOLT**

Specification

RECOMMENDED POLE SPACINGS CROSS SECTIONAL DIMENSIONS OF THE POLES CURRENT CONTROL DUTY CYCLE MAX CURRENT "ON" TIME SURFACE TEMPERATURE OF HANDLE TANGENTIAL FIELD STRENGTH (IN STEEL) AT 65mm POLE SPACING (110/230) TANGENTIAL FIELD STRENGTH (IN STEEL) AT 120mm POLE SPACING (110/230) **OVERALL DIMENSIONS – STANDARD UNIT** STANDARD MAINS LEAD LENGTH IAYSON MASS - STANDARD UNIT ENVIRONMENTAL PROTECTION DEGREE CE CERTIFICATION EN50081-2/1993 and EN55014:1993 LIFT CAPACITY

SAFETY PROTECTION

TRANSFORMERS

JAY GO 230V TO 110V STEP DOWN TRANSFORMER BUILT INTEGRALLY INTO A JAY/JAYSON CARRY CASE. IDEAL FOR SITE USE, THE CASE HAS AMPLE ROOM FOR INSPECTION AEROSOLS

230V TO 110V STEP DOWN (SINGLE SOCKET FOR 1 JAYSON) INCLUDING ROBUST CARRY CASE AND FUSED PROTECTION

230V TO 110V STEP DOWN (DOUBLE SOCKET FOR 2 JAYSONS) INCLUDING ROBUST CARRY CASE AND FUSED PROTECTION

TEST WEIGHTS

4.5KG STEEL WEIGHT WITH HANDLE (American and European AC Test)

SPARES SWITCH ONLY **MEMBRANE AND SURROUND** SWITCH ASSEMBLY (SWITCH, MEMBRANE AND SURROUND) FOOT LAMINATION (I PAIR) COMPLETE LEG ASSEMBLY (I PAIR FOOT AND MID ARM) **CABLE STRAIN RELIEF**

5 sec less than 40°C at max duty cycle (30°C Ambient) greater than or equal to 3.8kA/m greater than or equal to 2.0kA/m Length 220mm Height 205mm (legs straight) 4m 2.5Kg Tested to IP 56 Passed AC - All Models (American E1444-01 4.5Kg (44N) (Europe BS EN ISO 9934-3:2002 4.5Kg (44N) In built thermal auto re-set cut out PAT Test Certificate

65mm to 120mm (Max pole spacing 180mm)

ORDER CODE JAY GO

SST

DST

ORDER CODE 4.5Kg Test Weight

ORDER CODE

JAYSON - S JAYSON - M - SU JAYSON - S - M - SU **JAYSON - FOOT** JAYSON - LEG **JAYSON - CSR**

JOHNSON & ALLEN LTD, SMITHFIELD, SHEFFIELD, S3 7AR, ENGLAND Tel: +44 (0)114 273 8066 Fax: +44 (0)114 272 9842 Email: info@johnsonandallen.co.uk Web: www.johnsonandallen.co.uk