

Absolute digital dial indicators

- Measuring range: 0-50.8 mm.
- Resolution: 0.01 mm or 0.001 mm.
- mm/inch conversion.
- ABS/INC switchable.
- LCD display 330° rotatable.
- Digimatic data output.
- On/off switch.
- Reset/preset.
- Ceramic stylus tip.
- Max. measuring speed: any.
- Measuring force ≤ 2 N.
- Clamping stem: $\varnothing 8$ mm.
- Dial diameter: 60 mm.
- Reversible measuring direction.
- With determination of the reversal point (only 910.004).
- Adjustable tolerance limits (except 910.004).
- Flat back.

- With additional back with lug (only 909.998, 910.001/004).
- Protection: IP54.
- Delivery in a case with an inspection report.
- Power supply: 1 battery type CR2032.



NEW

PRICE




909.686



909.687



910.039/038



909.613



909.611



909.614

Item No.	Measuring range/mm	Resolution mm	Accuracy mm
909.998	0-12.7	0.001	± 0.004
909.999	0-25.4	0.001	± 0.005
910.000	0-50.8	0.001	± 0.006
910.001	0-12.7	0.01	± 0.01
910.002	0-25.4	0.01	± 0.01
910.003	0-50.8	0.01	± 0.015
For internal measurements:			
910.004	0-12.7	0.001	± 0.004
With Bluetooth:			
910.079	0-12.7	0.001	± 0.004
910.082	0-12.7	0.01	± 0.01
Options:			
495.157	Spare battery		
909.686	USB interface		
909.687	Footswitch for USB interface		
910.038	Wireless USB receiver		
910.039	Wireless sender		
909.611	Retraction lever		
909.613	Cable retraction device (1 m) (maximum travel 10 mm)		
909.614	Retraction lever (maximum travel 12.7 mm)		