

Digital depth micrometers IP65

Digital depth micrometers with interchangeable, spherical rods or flat rods. With the flat rods mainly flat and spherical surfaces can be measured very accurately. The spherical rods are especially suitable for beveled and hollow surfaces. The high accuracy of the rods makes resetting after exchanging the rods unnecessary. Two models with different base lengths available.

- Measuring range: 0-300 mm.
- Resolution: 0.001 mm.
- mm/inch conversion.
- ABS/INC switchable.
- Automatic switch-off.
- Preset.
- Measuring rods: $\varnothing 4.5$ mm.
- Locking screw.
- Protection: IP65.
- DIN 863 T2.
- Power supply: 1 battery type V357.



Model with spherical rods especially for hollow and beveled surfaces

Item No.	Item No.	Measuring range/mm	Accuracy mm	Number of rods
Base 63 mm:	Base 101.5 mm:			
909.753	909.759	0- 25	± 0.005	1
909.754	909.760	0- 50	± 0.005	2
909.755	909.761	0-100	± 0.006	4
909.756	909.762	0-150	± 0.007	6
909.757	909.763	0-200	± 0.008	8
909.758	909.764	0-300	± 0.009	12

Model with flat rods especially for flat and spherical surfaces

Item No.	Item No.	Measuring range/mm	Accuracy mm	Number of rods
Base 63 mm:	Base 101.5 mm:			
909.765	909.771	0- 25	± 0.005	1
909.766	909.772	0- 50	± 0.005	2
909.767	909.773	0-100	± 0.006	4
909.768	909.774	0-150	± 0.007	6
909.769	909.775	0-200	± 0.008	8
909.770	909.776	0-300	± 0.009	12

Option

Item No.	Description
836.535	Spare battery