Digital micrometers IP65

These digital micrometers have an IP65 classification and are therefore not only resistant to dust but can also withstand water jets. Also available as fast adjustable micrometers with a pitch of 2 mm.

- Measuring range: 0-300 mm.
- Resolution: 0.001 mm.
- mm/inch conversion.
- ABS/INC switchable.
- On/off switch.
- Automatic switch-off.

- Tungsten carbide measuring faces: Ø 6.5 mm.
- Protection: IP65.
- DIN 863 T1.
- From measuring range 25-50 mm including setting gauge.
- Power supply: 1 battery type V357.

Fast adjustable micrometers

 \blacksquare 1 revolution of the thimble = 2 mm.



Fast adjustable micrometers

| Item No. | Measuring range/mm | Accuracy mm | |
|--|-------------------------------------|--|--|
| 909.545 909.546 909.547 909.548 | 0- 25 25- 50 50- 75 75-100 | ± 0.002 ± 0.002 ± 0.003 ± 0.003 | |

Sets

| Item No. | Measuring range/mm | Pieces |
|----------|--------------------|--------|
| 909.577 | 0- 75 | 3 |
| 909.578 | 0 - 100 | 4 |
| 909.579 | 0 - 150 | 6 |

| Item No. | Measuring range/mm | Accuracy mm | |
|----------|--------------------|----------------|--|
| 909.549 | 0- 25 | ±0.002 | |
| 909.550 | 25 - 50 | ± 0.002 | |
| 909.551 | 50 - 75 | ± 0.003 | |
| 909.552 | 75 - 100 | ± 0.003 | |
| 909.556 | 100 - 125 | ± 0.003 | |
| 909.557 | 125 - 150 | ± 0.003 | |
| 909.558 | 150 - 175 | ± 0.004 | |
| 909.559 | 175 - 200 | ± 0.004 | |
| 909.560 | 200-225 | ± 0.004 | |
| 909.561 | 225 - 250 | ± 0.004 | |
| 909.562 | 250-275 | ± 0.005 | |
| 909.563 | 275 - 300 | ± 0.005 | |

Option:

836.535 Spare battery