



Premium force measuring instrument with graphic assisted display for tension and compression tests with external measuring cell

Features

- · Premium force gauge with external measuring cell, tension loops and compression plates included in delivery
- Turnable display with backlight
- · Peak-Hold function to capture peaks (measurement result will be "frozen" for a short time) or Track function mode for a continuous measurement indication (period of time approx. 10 s)
- Metal housing for durable usage in harsh environmental conditions
- Can be mounted on all SAUTER test stands
- · Capacity display: A bar lights up to show how much of the measuring range is still available
- · Measuring with tolerance range (limit-setting function): Upper and lower limiting can be programmed individually, in pull and push direction. The process is supported by an visual signal.
- Internal memory for up to 500 measurement
- Continuous analogue output: Linear voltage signal in dependence to the load (-2 to +2 V)
- · Selectable measuring units: N, kN, kg, oz, lbf
- ■ Delivered in a robust carrying case

Technical data

- Internal measuring frequency: 1000 Hz
- Precision: 0,2 % of [Max]
- Overload protection: 120 % of [Max]
- Dimensions housing: W×D×H 175×75×30 mm
- Dimensions load cell W×D×H 76,2×51×19 mm
- Thread: M12
- · Rechargeable battery pack integrated, standard, operating time up to 10 h without backlight, charging time approx. 8 h
- Net weight approx. 0,5 kg

Accessories

- Plug-In for data transfer of measuring data from the measuring instrument and transfer to a PC, e.g. in Microsoft Excel®, SAUTER AFI-1.0, € 90,-
- Force-displacement data transfer software with graphical representation of the measuring process, only in combination with SAUTER LD, SAUTER AFH LD, € 250,-
- Force-time data transfer software for graphical representation on the PC and data transfer to Microsoft Excel®, SAUTER AFH FAST, € 115,-
- Force-displacement data transfer software with graphic display of the measurement process, only in combination with SAUTER LB, SAUTER AFH FD, € 650,-
- USB cable, SAUTER FL-A01, € 49,-
- · RS-232 adapter cable, SAUTER FL-A04, € 49,-

































kS	ISO
YS	+4 DAYS

Model	Measuring range	Readout	Price	Option DAkkS calibration certificate (≤ 5 kN)/ Factory calibration certificates (< 5 kN)					
			excl. of VAT	Tensile force		Compressive force		Tensile/Compressive force	
	[Max]	[d]	ex works	DAkkS		DAkkS		DAkkS	
SAUTER	N	N	€	KERN	€	KERN	€	KERN	€
FL 2K	2500	1	600,-	963-162	165,-	963-262	165,-	963-362	300,-
FL 5K	5000	1	990,-	963-163	225,-	963-263	225,-	963-363	405,-
FL 10K	10000	2	1150,-	961-164	295,-	-	-	-	_
FL 20K	20000	5	1190,-	961-164	295,-	_	-	-	-