

Absolute digital dial indicators

Absolute digital dial indicators with a function to set tolerance limits with clear optical Go (NoGo) reading.

- Measuring range: 0 - 50 mm.
- Resolution: 0.01 mm or 0.001 mm.
- mm/inch conversion.
- ABS/INC switchable.
- With data output.
- Adjustable tolerance limits.
- **Tolerance display** by means of illuminated green LED at GO value.
- On/off switch.
- Reset/preset.
- Ceramic stylus tip.
- Max. measuring speed: unlimited.
- Clamping stem: $\varnothing 8$ mm.
- Dial diameter: 60 mm.
- Reversible measuring direction.
- Flat back and additional back with lug.
- Protection: IP54.
- Delivery with a manufacturer measuring report.
- Power supply: 1 battery type CR2032.



QControl
We Measure Quality



906.870



906.618

USB interface:


- For data transfer to PC (e.g. Excel, Word).
- Operating system: Windows and other.
- PC connection: USB.
- No software or driver to install.
- Foot switch (optional).



909.687



906.619/910.038



909.613



909.614

Item No.	Measuring range/mm	Resolution mm	Accuracy mm	Price EUR
910.221	0 - 12.7	0.001	± 0.004	
910.222	0 - 25.4	0.001	± 0.004	
910.223	0 - 50.8	0.001	± 0.005	
906.870	0 - 12.7	0.01	± 0.01	
906.871	0 - 25.4	0.01	± 0.01	
906.872	0 - 50.8	0.01	± 0.015	
Options:				
495.157	Spare battery type CR2032			
906.618 ^{1,2}	USB interface			
909.687	Footswitch for USB interface			
910.038	Wireless USB receiver			
906.619 ²	Wireless transmitter			
909.611	Retraction lever			
909.613	Cable retraction device (0.4 m) (maximum travel 10 mm)			
909.614	Retraction lever (maximum travel 12.7 mm)			

¹ Standard configured for PC with English (US) keyboard.
Also available on request for alternative keyboards.

² With micro-USB connection.