Digital height and scribing gauges

- Measuring range: 0-1000 mm.
- Resolution: 0.01 mm.
- mm/inch conversion.
- ABS/INC switchable.
- On/off switch.
- Reset.
- Hold function.
- Fine adjustment.

- Delivery incl. scriber.
- Power supply:

909.244/245/246: 1 battery type V357, 906.267/268: 1 battery type CR2032.

From measuring range 500 mm:

- Tolerance function.
- Preset.



Item No.	Measuring range/mm	Accuracy mm	Price EUR
906.267	0- 200	±0.03	
906.268	0 - 300	± 0.04	
909.244	0- 500	±0.05	
909.245	0- 600	± 0.07	
909.246	0 - 1000	± 0.07	

Ontions:

Options	
836.535	Spare battery type V357
495.157	Spare battery type CR2032
906.029	Scriber for 906.267
906.049	Scriber for 906.268
906.054	Scriber for 909.244
906.075	Scriber for 909.245
906.077	Scriber for 909.246



Absolute digital height and scribing gauges

Digital height and scribing gauges with an absolute measuring system.

- Measuring range: 0-600 mm.
- Resolution: 0.01 mm.
- Handwheel drive for easy head displacement.
- Interchangeable scriber, intake 9 x 9 mm.
- ABS/INC switchable.
- Digimatic data output.
- On/off switch.
- Reset.
- Hold function.Locking screw.

- Delivery incl. scriber, dial indicator holder and Digimatic data cable.
- Power supply: 1 battery type CR2032.

USB interface:

- For data transfer to PC (e.g. Excel, Word).
- Operating system:
- Windows and other.
- PC connection: USB.No software or driver to install.
- Foot switch (optional).











			,
Item No.	Measuring range/mm	Accuracy mm	Price EUR
910.096	0-300	0.03	
910.097	0 - 600	0.05	
With Bluet	ooth:		
910.098	0-300	0.03	

Options:

495.157 Spare battery

909.686 USB interface

909.687 Footswitch for USB interface

910.038 Wireless USB receiver

910.039 Wireless transmitter

906.256 Scriber

Special digital height and scribing gauges

The dual display model shows the measuring value on the displays on both sides of the instrument, ideal for left handed use. The magnetic base model is made primarily of plastic, which makes it very light and easy to handle. Due to the magnets in the flat plastic base the instrument can also be placed on magnetic surfaces at an angle.

- Measuring range: 0-150 mm.
- Resolution: 0.01 mm.
- mm/inch conversion.
- On/off switch.
- Delivery incl. scriber.
- Double display (906.225).
- Magnetic base (906.226).



Item No.	Accuracy/mm	Price EUR
906.225	±0.03	
906.226	± 0.4	
Options	:	
836.535	Spare battery type V35	57
495.157	Spare battery type CR	2032
906.344	Scriber for 906.225	
906.354	Scriber for 906.226	

Power supply:906.225: 1 battery type V357,906.226: 1 battery type CR2032.



Digital height and scribing gauge with dial indicator holder

Solid and stable instrument with integrated dial indicator holder and stainless measuring table.

- Measuring range: 0-500 mm.
- Resolution: 0.01 mm.
- mm/inch conversion.
- ABS/INC switchable.
- On/off switch.
- Preset.
- Reset.
- Hold function.
- Tolerance function.
- Fine adjustment.
- Intake scriber: 8 x 6 mm.
- Delivery incl. scriber.



Item No.	Measuring range/mm	Accuracy mm	Price EUR
906.115 906.116	0-200 0-300	±0.04 ±0.04	
906.117	0-500	± 0.04 ± 0.06	

Options:

836.535 Spare battery 906.343 Scriber

Dial gauge clamping shaft 8 mm.
Measuring table: 906.115/116: 80

■ Measuring table: 906.115/116: 80 x 80 mm, 906.117: 110 x 100 mm.

ower supply: 1 battery type V357.





Digital double columns height and scribing gauges

This is a very stable digital height gauge because of its twin guide system. The measuring unit moves over two independent columns with high precision toothed racks, which generates an accurate measurement.

- Measuring range: 0-600 mm.
- Resolution: 0.01 mm.
- Repeatability: 0.01 mm.
- Handwheel drive for easy head displacement.
- mm/inch conversion.
- ABS/INC switchable.
- On/off switch.
- Reset/preset.
- Intake scriber: 9 x 9 mm.
- Delivery incl. scriber.
- Power supply: 1 battery type V357.





Item No.	Measuring range/mm	Accuracy mm	Price EUR
906.263	0-300	±0.04	
906.264	0-500	± 0.05	
906.265	0-600	± 0.05	

Option:

836.535 Spare battery 906.118 Scriber 9 x 9 mm

