

Dino-Lite
Digital Microscope
The Industry Standard

DINO-LITE PRODUCT RANGE FOR:

Art and paper restorers,
conservators, antique collectors,
museums and archeologists



APPLICATIONS

The Dino-Lite digital microscopes are tailored for a broad range of user groups. In the art and paper restorers business the following target groups can be distinguished:


- Painting and art restorers
- > Art and antique collectors
- > Museums
- > Forensic departments
- > Auction houses
- > Archeologists
- > Palaeontologist

A PROFESSIONAL SOLUTION

Professional solution for inspection, quality control, classifying and working on art, paintings, ancient relics, antiques or old coins. The series with long working distance of up to 15 cm enables the user to work under the microscope. The built-in adjustable polarizer helps to reduce glare on shiny objects. Available in composite or full aluminum alloy housing.

A POWERFUL TOOL

Dino-Lite has developed a special range of microscopes and accessories, tailored to fit the needs of art and paper restorers and everybody working with art, paintings, ancient relics, antiques, old coins, etc. The Dino-Lite products are available for professionals as well as for hobbyists. Specially designed models with UV light, infrared light or built-in polarizer make it an ideal solution for inspection and working on all kinds of art and antique. Bundled with the DinoCapture software for Windows or DinoXcope software for Apple Macintosh, the Dino-Lite is a very powerful and easy to use tool.



THE DINO-LITE IS VERY USEFUL
FOR ANALYZING AND RESTORING
PAINTINGS, DOCUMENTS, TEXTILES
AND OTHER OBJECTS OF ART.




DINO-LITE SOFTWARE

More info: www.dino-lite.eu/support/software

ADVANCED SOFTWARE INCLUDED

A professional, reliable software environment is essential when working with computer accessories like an USB microscope. All Dino-Lite USB products are equipped with an in-house developed software suite. The Dino-Capture software is continuously developed, is free of charge for Dino-Lite users and has an automatic update feature. DinoCapture software is available for Windows and DinoXcope for Macintosh computers. DinoCapture software is intuitive, user-friendly and can be used without hardly any training. Free online & e-mail software support is available.



LANGUAGES

The DinoCapture 2.0 software is available in many languages, such as: English, German, French, Spanish, Chinese, Japanese, Portuguese, Italian, Russian, Dutch, Greek, Hungarian, Polish, Romanian, Swedish, Finnish, Danish, Czech, Croatian, Norwegian, Turkish.

MAIN SOFTWARE FEATURES

- > Capturing photographs, videos or time-lapsed videos
 - > Saving pictures in several formats
 - > Advanced image processing
 - > Measurement options like: line, radius, circle, 3-point circle, angle, etc.
 - > Measurements on captured images or on live images
 - > Calibration options
 - > E-mail integration
 - > Adding notes and markings on images
 - > Skype integration for real-time on-line sharing with suppliers, customers or colleagues
 - > Connect multiple Dino-Lite microscopes
 - > Controlling lighting options from the software
 - > IP functionality for remote viewing of microscopic images
 - > Barcode/QR code recognition functionality
 - > GPS integration
-

DINO-LITE UNIVERSAL

More info: www.dino-lite.eu/universal

AM4113ZT

The main features of the AM4113ZT are:

1.3 Megapixel sensor | USB 2.0 connection | 10-70x & 200x magnification | Adjustable integrated polarizer | 8 white switchable white LEDs | Extensive measurement functionality | Calibrated measurements



1.3 MEGAPIXEL
1280 x 1024



USB 2.0



ADJUSTABLE
~10-70x & 200x



POLARIZER
ANTI-REFLECTION



8 WHITE LEDS
SWITCHABLE



MEASUREMENT
FUNCTIONALITY



STANDARD
WORKING
DISTANCE

AM4013MZT

The main features of the AM4013MZT are:

1.3 Megapixel sensor | USB 2.0 connection | 10-70x & 200x magnification | Adjustable integrated polarizer | 8 white switchable white LEDs | Metal housing, Extensive measurement functionality | Calibrated measurements.



1.3 MEGAPIXEL
1280 x 1024



USB 2.0



ADJUSTABLE
~10-70x & 200x



POLARIZER
ANTI-REFLECTION



8 WHITE LEDS
SWITCHABLE



MEASUREMENT
FUNCTIONALITY



STANDARD
WORKING
DISTANCE

AM4515ZT

The main features of the AM4515ZT are:

1.3 Megapixel sensor | USB 2.0 connection | 20-220x magnification
Adjustable integrated polarizer | 8 white switchable white LEDs
Automatic Magnification Reading (AMR) | Extensive measurement
functionality | Calibrated measurements | Exchangeable caps.



1.3 MEGAPIXEL
1280 x 1024



USB 2.0



ADJUSTABLE
~20-220x



POLARIZER
ANTI-REFLECTION



8 WHITE LEDS
SWITCHABLE



AUTOMATIC
MAGNIFICATION
READING
AMR



MEASUREMENT
FUNCTIONALITY



STANDARD
WORKING
DISTANCE



EXCHANGEABLE
CAP

AM7915MZT

The main features of the AM7915MZT are:

5 Megapixel sensor | USB 2.0 connection | 10-220x magnification
Adjustable integrated polarizer | 8 white switchable white LEDs
Metal housing | Flexible LED Control (FLC) | Extended Depth of Field (EDOF) | Extended Dynamic Range (EDR) | Automatic Magnification Reading (AMR) | Extensive measurement functionality | Calibrated measurements | Exchangeable caps.



5 MEGAPIXEL
2592 x 1944



USB 2.0



ADJUSTABLE
~10-220x



POLARIZER
ANTI-REFLECTION



8 WHITE LEDS
SWITCHABLE



METAL
HOUSING



FLEXIBLE
LED CONTROL
FLC



EXTENDED
DEPTH OF FIELD
EDOF



EXTENDED
DYNAMIC RANGE
EDR



AUTOMATIC
MAGNIFICATION
READING
AMR



MEASUREMENT
FUNCTIONALITY



EXCHANGEABLE
CAP

DINO-LITE LONG WORKING DISTANCE

More info: www.dino-lite.eu/longworkingdistance

AM4113ZTL

The main features of the AM4113ZTL are:

1.3 Megapixel sensor | USB 2.0 connection | 10-90x magnification
Long Working Distance (LWD) | Adjustable integrated polarizer
8 white switchable white LEDs | Extensive measurement functionality
Calibrated measurements.



1.3 MEGAPIXEL
1280 x 1024



USB 2.0



CONTINUOUS
~10x-90x



4-15 cm

LONG WORKING
DISTANCE



POLARIZER
ANTI-REFLECTION



8 WHITE LEDS
SWITCHABLE



MEASUREMENT
FUNCTIONALITY



EXCHANGEABLE
CAP

AM4013MZTL

The main features of the AM4013MZTL are:

1.3 Megapixel sensor | USB 2.0 connection | 10-90x magnification
Long Working Distance (LWD) | Adjustable integrated polarizer
8 white switchable white LEDs | Metal housing | Extensive
measurement functionality | Calibrated measurements.



1.3 MEGAPIXEL
1280 x 1024



USB 2.0



CONTINUOUS
~10x-90x



4-15 cm

LONG WORKING
DISTANCE



POLARIZER
ANTI-REFLECTION



8 WHITE LEDS
SWITCHABLE



METAL
HOUSING



MEASUREMENT
FUNCTIONALITY




EXCHANGEABLE
CAP

AM4515ZTL

The main features of the AM4515ZTL are:


1.3 Megapixel sensor | USB 2.0 connection | 10-140x magnification
Adjustable integrated polarizer | 8 white switchable white LEDs
Automatic Magnification Reading (AMR) | Extensive measurement
functionality | Calibrated measurements | Exchangeable caps.



AM7915MZTL

The main features of the AM7915MZTL are:

5 Megapixel sensor | USB 2.0 connection | 10-140x magnification
Long Working Distance (LWD) | Adjustable integrated polarizer
8 white switchable white LEDs | Metal housing | Flexible LED Control
(FLC) | Extended Depth of Field (EDOF) | Extended Dynamic Range
(EDR) | Automatic Magnification Reading (AMR) | Extensive
measurement functionality | Calibrated measurements | Exchange-
able caps.



DINO-LITE SPECIAL LIGHTING

More info: www.dino-lite.eu/speciallighting

AM4113T-FVW

The main features of the AM4113T-FVW are:

1.3 Megapixel sensor | USB 2.0 connection | 10-70x & 200x magnification | Ultraviolet (UV) LEDs with 390-400nm | 4 white / 4 UV LEDs | Extensive measurement functionality | Calibrated measurements.



1.3 MEGAPIXEL
1280 x 1024



USB 2.0



ADJUSTABLE
~10-70x & 200x



UV-LEDs
390~400 nm



SWITCHABLE
UV/WHITE LEDs



MEASUREMENT
FUNCTIONALITY



STANDARD
WORKING
DISTANCE

AD4113T-I2V

The main features of the AD4113T-I2V are:

1.3 Megapixel sensor | USB 2.0 connection | 20-200x magnification | Ultraviolet (UV) 390nm and Near-infrared (NIR) 940nm LEDs | 4 Ultraviolet (UV) / 4 Near-infrared (NIR) LEDs | Extensive measurement functionality | Calibrated measurements | Exchangeable caps.



1.3 MEGAPIXEL
1280 x 1024



USB 2.0



ADJUSTABLE
~20-200x



UV-LEDs
400 nm



INFRARED
LEDs ~940nm



SWITCHABLE
UV/IR LEDs



MEASUREMENT
FUNCTIONALITY



EXCHANGEABLE
CAP

AM4115T-FVW

The main features of the AM4115T-FVW are:

1.3 Megapixel sensor | USB 2.0 connection | 20-220x magnification
Ultraviolet (UV) LEDs with 390-400nm | 4 white / 4 UV LEDs | Extensive
measurement functionality | Calibrated measurements | Exchange-
able caps.

AM7115MT-FUW

The main features of the AM7115MT-FUW are:

5 Megapixel sensor | USB 2.0 connection | 20-220x magnification
Ultraviolet (UV) LEDs with 375nm | 4 white / 4 UV LEDs | Metal
housing | Extensive measurement functionality | Calibrated
measurements | Exchangeable caps.



DINO-LITE EYEPIECE

More info: www.dino-lite.eu/eyepiece

EYEPIECE CAMERAS

With the DinoEye eyepiece cameras you can turn your conventional microscope into a digital microscope. You can easily replace the ocular (eyepiece) of your non-digital microscope with the DinoEye eyepiece and connect it via USB to your computer.

The DinoEye TV models can be connected straight into your TV using a TV connection. With the included proprietary DinoCapture software you have a professional software environment for image or video processing, including calibrated measurement features (USB models only).



AM4025X

The AM4025X has different adapters to fit microscopes with 23, 30 or 30,5 mm eyepieces. The DinoCapture software is bundled with the product.



USB 2.0



MEASUREMENT
FUNCTIONALITY



FITS 23, 30, 30,5 mm
OCULARS



1.3 MEGAPIXEL
1280 x 1024



CONNECTS
TO C-MOUNT



AM7025X

The DinoEye Edge 5MP eyepiece camera provides superior image quality and true colour reproduction.



USB 2.0



MEASUREMENT
FUNCTIONALITY



FITS 23, 30, 30,5 mm
OCULARS



5 MEGAPIXEL
2592 x 1944



CONNECTS
TO C-MOUNT



DINO-LITE ACCESSORIES

More info: www.dino-lite.eu/accessories



RK-06A

The Dino-Lite RK-06A stand is a sturdy and stable mid-range stand solution that can be used with all Dino-Lite digital microscopes. It is constructed of stainless steel and lightweight aluminum and offers precise focus adjustment as well as a quick vertical release function.



RK-10A

The Dino-Lite RK-10A stand is a sturdy and stable high-range stand solution that can be used with all Dino-Lite digital microscopes. It is constructed of stainless steel and lightweight aluminum and offers precise focus adjustment as well as a quick vertical release function.



RK-10-FX

The RK-10-FX is an optional flexible arm extension for the RK-06A and the RK-10A stand.



RK-10-PX

The RK-10-PX is a XY positioning arm with accurate and smooth adjustment options. It is a great add-on to the high precision RK-10A and the RK-06A stand.



RK-10-EX

The RK-10-EX is an optional horizontal arm attachment for the RK-06A and the RK-10A stand.



RK-10-VX

RK-10-VX is an optional vertical arm attachment for the RK-06A and the RK-10A stand.

DINO-LITE ACCESSORIES

More info: www.dino-lite.eu/accessories



MS52BA2

Dino-Lite heavy duty jointed flex arm stand. The MS52BA2 is a jointed articulating flex-arm type stand with holster for use with the Dino-Lite hand held digital microscopes.



SW-F1

Foot pedal accessory allowing you to take a picture with your foot.



RK-02

The RK-02 is a durable gooseneck stand solution designed for flexible and versatile usage with a Dino-Lite digital microscope. The C-clamp of the RK-02 fits to virtually any surface of up to 7 cm (~3 inch) thick, and can be mounted horizontally or vertically.



WF-10

The WF-10 WiFi Streamer allows Dino-Lite USB 2.0 models to be used wirelessly in connection with an iOS (iPhone/iPad) or Android app on a tablet, smartphone, or computer.