

Internal measuring instruments

Internal measuring instruments for measurements of bores, internal grooves and other hard-to-reach places.

- Measuring range: 5 - 60 mm.
- Graduation: 0.01 mm.
- Rotatable dial.
- Adjustable tolerance markers.
- Measuring faces with different contact forms.



Item No.	Measuring range/mm	Accuracy mm	Length/mm			Contact form/mm
			L	A	B	
Travel 10 mm:						
908.830	5 - 15	±0.02	20	1	1.5	① R 0.3
908.831	10 - 20	±0.02	25	1.5	3.0	① R 0.3
908.832	20 - 30	±0.02	30	2	6.5	① R 0.5
908.833	30 - 40	±0.02	30	2.5	9.0	① R 0.5
908.834	40 - 50	±0.02	30	2.5	9.0	① R 0.5
908.836	10 - 20	±0.02	25	1.5	3.0	② ø1.5
908.837	20 - 30	±0.02	30	2	6.5	② ø1.5
908.838	30 - 40	±0.02	30	2.5	9.0	② ø1.5
908.839	40 - 50	±0.02	30	2.5	9.0	② ø1.5
Travel 20 mm:						
908.840	5 - 25	±0.03	35	1	1.5	① R 0.3
908.841	10 - 30	±0.03	55	2	3.5	① R 0.5
908.842	20 - 40	±0.03	80	3	6.5	① R 0.5
908.843	30 - 50	±0.03	80	3	8.5	① R 0.5
908.844	40 - 60	±0.03	80	3	8.5	① R 0.5
908.846	10 - 30	±0.03	55	2	3.5	② ø1.5
908.847	20 - 40	±0.03	80	3	6.5	② ø1.5
908.848	30 - 50	±0.03	80	3	8.5	② ø1.5
908.849	40 - 60	±0.03	80	3	8.5	② ø1.5

