

EPWLI

EPWLI "LOGISTIC" STAINLESS STEEL PALLET-WEIGHING FLOOR SCALES SERIES



Quick and accurate stainless steel pallet weighing scales, easy to use and transport. Integrated extractable weight indicator complete of stretchable connection cable which may be easily positioned according to one's weighing requirements. The automatic multirange capacity allows the maximum accuracy on the lower weight values, maintaining the same load capacity. Available also in dual range APPROVED version, for legal for trade use.

INOX IP68

CE M

The best solution
for advanced industrial
applications

MAIN FEATURES

- Weight indicator with support bracket having an adjustable inclination, for use on the column (optional), wall (optional adjustable support) or table.
- Stainless steel IP68 case, easy to clean and resistant in harsh and corrosive environments.
- Waterproof 5-key functional keypad.
- LCD 25mm backlit display with 6 high contrast digits and icons for indication of active functions.
- Functions with 4 shear beam 1000 Ohm stainless steel load cells approved according to OIML R60 C3 standards (3000+3000 divisions), IP68 protection degree, able to handle double the nominal load.
- Sheet-stainless steel structure and load surface, complete of adjustable feet.
- Level, wheels, and transport handle.
- Connection cable to the indicator, 3 m long.
- Accuracy: +/-0,05% of the capacity.
- Digital calibration and Set-Up from keypad or from PC through DINITOOLS.
- Power supply 110-240Vac.

SELECTABLE AND KEYPAD FUNCTIONS

- Clearing; automatic and manual tare, print.
- X 10 High resolution visualisation.
- Net/Gross or lb/kg conversion.
- Accumulation.
- Formula weighing.
- +/- Checkweighing.
- Percentage weighing.
- Alibi, for approved weigh transmission (optional).
- Counting.
- Input/Output.

I/O SECTION:

- RS232/C bidirectional port on RJ connector (or USB optionally) for quick or RS485 connection, configurable for PC, PLC, additional remote display.
- RS232/C bidirectional port for connection to printer or labeller.
- IR input for remote control management.

AVAILABLE ACCESSORIES

- Infrared remote control.
- Support column for indicator.

DIMENSIONS mm

- Values in mm



VERSIONS

Available models

Code	l x w x h (mm)	Max (kg)	d (kg)	CE-M 2x3000e (kg)
EPWLI	1260x800x75	600/1500/2000	0,2/0,5/1	-
EPWLIM M	1260x800x75	1000/2000	-	0,5/1



www.diniargeo.com



“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

DINI ARGEO
FRANCE sarl
Nogent-sur-Marne
info.fr@diniargeo.com

DINI ARGEO
GMBH
Sinsheim - Germany
info.de@diniargeo.com

DINI ARGEO
UK Ltd
Taunton - United Kingdom
info.uk@diniargeo.com

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
Shanghai - China
info.cn@diniargeo.com

DINI ARGEO
WEIGHBRIDGES
Calto (RO) – Italy
info@diniargeo.com



HEAD OFFICE

Via Della Fisica, 20
41042 Spezzano di Fiorano Modena - Italy
Tel. +39.0536 843418 Fax. +39.0536 843521
info@diniargeo.com

SERVICE ASSISTANCE

Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena - Italy
Tel. +39.0536 921784 Fax. +39.0536 926654
service@diniargeo.com



SALES AND TECHNICAL ASSISTANCE SERVICE