

DFWLB

"DFWLB": MULTIFUNCTION IP68 WEIGHT INDICATOR FOR INDUSTRY



Digital weight indicator for industrial environments, easy to install and use. The IP68 protection degree and the built-in long life battery make it particularly suitable for automotive and mobile weighing applications. Standard fitted with a support bracket with adjustable inclination. CE-M approvable (OIML R-76 / EN 45501).

Working in cooperation with:

QCONTROL LTD QUALITY SOLUTIONS

51-53 AGAMEMNONOS STR. - 17675 - KALLITHEA, ATHENS
Tel. 0030-2109416200 Fax. 0030-2109415211
info@qcontrol.gr

The best solution
for advanced industrial
applications

MAIN FEATURES

- 5-key functional waterproof keypad.
- Backlit 25mm LCD display with 6 high contrast digits with icons for showing the active functions.
- Easy to clean ABS IP68 case, resistant to harsh and corrosive environments.
- Suitable for use on the table, column, or wall.
- Fitted with fixing bracket with adjustable inclination.
- A/D 24 bit, 4 channel converter, max. 200 conv./sec. autoselect, and up to 8 signal linearisation points.
- Up to 10.000e or multirange 3 x 3000e @ 0,3 μ V/d in CE-M approved versions for legal for trade use.
- Up to 1.000.000 displayable divisions with internal resolution up to 3.000.000 points.
- Connection with up to 8 load cells with input resistance equal to 350 Ohm or up to 16 cells of 700 Ohm each.
- Digital calibration and Set-Up from keypad or from PC through DINITOOLS.
- Power supply through built-in rechargeable battery, with 60h operating time, and fitted with external 12Vdc battery charger.

MAIN CERTIFICATIONS

- EC Type Approval (EN45501)
- OIML R76

FUNCTIONS

- MAIN FUNCTIONS:
 - Zeroing
 - Automatic tare
 - Presetable tare
 - Printing in 1, 2 or 3 copies
 - Data transmission to PC.
- OPERATING MODES:
 - High Resolution Weighing x 10
 - Net/Gross or lb/kg conversion
 - Accumulation
 - Formula weighing
 - +/- Checkweighing
 - Percentage weighing
 - Approved transmission of the weight to PC/PLC or data recording on MMC/USB (with Alibi memory ALMEM option)
 - Counting
 - In/Out Truck weighing
 - Hold and Peak.

I/O SECTION

- RS232/C bidirectional port on RJ connector for quick connection (optional RS485) on screw terminal, configurable for PC, PLC, or additional remote display.
- RS232/C bidirectional port configurable for connection to printer or labeller.



www.diniargeo.com



“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

DINI ARGEO
FRANCE sarl
Nogent-sur-Marne

DINI ARGEO
GMBH
Sinsheim - Germany

DINI ARGEO
UK Ltd
Taunton - United Kingdom

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
Shanghai - China

DINI ARGEO
WEIGHBRIDGES
Calto (RO) – Italy



HEAD OFFICE
Via Della Fisica, 20
41042 Spezzano di Fiorano Modena - Italy



QCONTROL LTD QUALITY SOLUTIONS

51-53 AGAMEMNONOS STR. - 17675 - KALLITHEA, ATHENS

Tel. 0030-2109416200 Fax. 0030-2109415211

info@qcontrol.gr

SALES AND TECHNICAL ASSISTANCE SERVICE