PROFESSIONAL MEASURING
SINCE 1844

KERN

Product brochure

31.10.2026

# KERN FPE 15K-3

Entry-level bench scale with stainless steel weighing plate and checkweighing function

ENGLISH




## CONTACT

**KERN & SOHN GmbH**
**Ziegelei 1**
**72336 Balingen**
**Germany**

**+49 7433 9933-0**
**info@kern-sohn.com**
**www.kern-sohn.com**







## APPLICATION EXAMPLE





## FEATURES

- Weighing with tolerance range (checkweighing): a visual signal helps with portioning, dispensing or grading
- Stainless steel weighing plate, which makes cleaning easy and hygienic
- Integrated piece-counting function with storable piece weight
- Sleep function: The scale automatically switches to energy-saving mode after an adjustable period of inactivity

## TECHNICAL DATA

- Large backlit LCD display, digit height 25 mm
- Dimensions weighing surface, stainless steel, W×D 190×230 mm
- Net weight approx. 1,8 kg
- Permissible ambient temperature -10 °C/40 °C

## MAIN SCOPE OF APPLICATIONS

- Food industry
- Gastronomy
- Dietetics
- educational institutions

## PICTOGRAMS

Standard




Option




## MODEL OVERVIEW

| Model | Weighing capacity [Max] | Readability [d] | Verification value [e] | Minimal load [Min] | Reproducibility | Linearity | Dimensions weighing surface |
|---|---|---|---|---|---|---|---|
| FPE 15K-3 | 15 kg | 0,001 kg | | | 0,001 kg | ± 0,003 kg | 190×230 mm |
| FPE 15K-3M | 15 kg | 0,005 kg | 0,005 kg | 0,1 kg | 0,005 kg | ± 0,015 kg | 190×230 mm |
| FPE 30K-2M | 30 kg | 0,01 kg | 0,01 kg | 0,2 kg | 0,01 kg | ± 0,03 kg | 190×230 mm |
| FPE 30K-3 | 30 kg | 0,002 kg | | | 0,002 kg | ± 0,006 kg | 190×230 mm |
| FPE 3K-3M | 3000 g | 1 g | 1 g | 20 g | 1 g | ± 3 g | 190×230 mm |
| FPE 3K-4 | 3000 g | 0,2 g | | | 0,2 g | ± 0,6 g | 190×230 mm |
| FPE 6K-3 | 6000 g | 0,5 g | | | 0,5 g | ± 1,5 g | 190×230 mm |
| FPE 6K-3M | 6000 g | 2 g | 2 g | 40 g | 2 g | ± 6 g | 190×230 mm |

## ACCESSORIES

| Model | Description |
|---|---|
| YKR-07-A | Rechargeable battery pack YKR-07-A (Li-Ion, 3,7 V, 4.000 mAh) |

## SERVICES

| Model | Description |
|---|---|
| 961-248 | Adjustment at the location of installation 961-248 (Not in combination with verification) |
| 963-128 | DAkkS calibration certificate 963-128 |
| 969-517 | Confirmation of the manufacturer’s specification (only in combination with DAkkS calibration certificate)969-517 |
| 970-012 | Warranty extension (+2 years) 970-012 |

ENGLISH

# KERN Pictogram Overview

| | |
|---|---|
|  | External adjustment: Adjusting accuracy using external adjustment weight |
|  | Piece counting: Reference quantities selectable. Display can be switched from piece to weight |
|  | Units can be switched to e.g. non-metric units |
|  | Measuring with tolerance range (checkweighing): Upper and lower limit values can be programmed, e.g. for sorting, portioning or for measuring coatings or material thicknesses. The process is supported by an acoustic and/or optical signal |
|  | Plug-in power supply: 230V/50Hz in standard version for EU, CH. On request GB, USA or AUS version available |
|  | Weighing principle Strain gauges: Electrical resistor on an elastic deforming body |
|   | Package shipment by courier service: The duration of internal product provision is one day |
|  | Rechargeable battery pack: Rechargeable set |
|   | Accredited calibration (DKD): The duration of the accredited calibration is 3 working days |

ENGLISH